

Welcome to the ZIPWALL® family of fine dust control products.

This new and improved ZipWall® Zipper has been redesigned to provide you with stronger adhesion and with easier opening and closing capabilities from either side of the dust barrier you have constructed.


ZipWall® Zipper installation instructions.

1. After the ZipWall® barrier system is constructed, select where you want the doorway opening to be.



2. Be sure the plastic or barrier material is clean. Hold the zipper up to the plastic to determine where you want it. **The pulls should be at the bottom!** Be sure the entire length of the zipper has plastic to stick to. Then start to peel the paper from the back of the zipper at the top and begin to press the zipper onto the plastic.

3. Remove the paper as you press the zipper onto the plastic. Remember to keep it as straight as possible. At the bottom of the zipper, separate the two sides of the zipper to be sure both pulls are free of the adhesive. **The inside pull should not be stuck to the Zipper.**



4. Carefully unzip the zipper completely. Then, using the opening as a guide, cut the plastic to make the doorway.

5. Now that the zipper is open and the plastic is cut, run your fingers up and down the plastic and the zipper to ensure a tight bond. If possible, allow a few minutes for the adhesive to set before zipping it back together.



6. For a wide doorway, install another zipper on the plastic as far away from the first zipper as you want the opening to be. After both zippers are installed and opened, use the enclosed string to tie up the loose plastic at the top of the doorway.

7. Works best in temperatures above freezing.

More ZIPWALL® dust control products



ZipWall Kits: 2 Poles and 2 Jacks per kit. Available in 2 sizes:

1. Standard: (Kit 12) contains 2 three section telescopic poles 4 feet long that extends to 12 feet. 2. Special (Kit 20) contains 2 four section telescopic poles 5 feet long that extends to 20 feet.

With Jacks attached to poles, Kit 12 reaches 13 feet fully extended and Kit 20 reaches 21 feet fully extended.

GripDisks: For use when constructing a ZipWall dust barrier on floors that are highly polished such as marble or coated wood.

The GripDisk, when positioned on the floor and under the plastic sheeting held by the ZipWall Pole, will not slide.



Carrying Bag: This attractive and sturdy nylon bag was made to hold six Standard (K-12) ZipWall Poles with six Jacks attached. It can also carry six Special (K-20) Poles with six Jacks unattached. Many contractors have told us how important these bags have been in keeping their ZipWall products well organized.

